Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016		
1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING				
Product name	: Ondina X 420			
Product code	: 001E2771			
CAS-No.	: 1262661-88-0			
Manufacturer or supplier's	details			
Manufacturer/Supplier	<ul> <li>LLC Shell Neft Russian Federation, 125445, Moscow, Smolnaya,24/D</li> </ul>			
Telephone Telefax	: (+7) 4952586900 : (+7) 4952586920			
Emergency telephone number	: +44(0)1235 239670			
Recommended use of the chemical and restrictions on use				
Recommended use	: Process oil.			

## 2. HAZARDS IDENTIFICATION

Classification (REGULATION (EC) No 1272/2008)			
Aspiration hazard	: Category 1		
Label elements Hazard pictograms :	•		
Signal word	: Danger		
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: H304 May be fatal if swallowed and enters airways. ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria.</li> </ul>		
Precautionary statements	<ul> <li>Prevention: No precautionary phrases.</li> <li>Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.</li> <li>P331 Do NOT induce vomiting.</li> <li>Storage:</li> </ul>		

Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016

P405 Store locked up. **Disposal:** P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities. Not classified as flammable but will burn.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Substance
Chemical nature	:	Fischer-Tropsch derived base oil, consisting largely of branched, cyclic and linear hydrocarbons having carbon numbers in the range of C18 to C50.

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Distillates (Fischer- Tropsch), heavy, C18- 50- branched and linear	1262661-88-0		Asp. Tox. 1; H304	<= 100

For explanation of abbreviations see section 16.

### Other information

Refer to Chapter 8 for Occupational Exposure Guidelines.

### 4. FIRST-AID MEASURES

If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
If swallowed	: If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear

Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016
	within the next 6 hours, transport facility: fever greater than 101° F breath, chest congestion or conti	(38.3°C), shortness of
Most important symptoms and effects, both acute and delayed	<ul> <li>If material enters lungs, signs and coughing, choking, wheezing, diff congestion, shortness of breath, a The onset of respiratory symptom several hours after exposure.</li> <li>Defatting dermatitis signs and sym burning sensation and/or a dried/ Ingestion may result in nausea, v</li> </ul>	iculty in breathing, chest and/or fever. Is may be delayed for mptoms may include a cracked appearance.
Protection of first-aiders	: When administering first aid, ensi- appropriate personal protective e incident, injury and surroundings.	quipment according to the
Notes to physician	: Treat symptomatically. Call a doctor or poison control ce	nter for guidance.

## 5. FIRE-FIGHTING MEASURES

Ignition temperature : > 320 °C / 608 °F	
Upper explosion limit : Typical 10 %(V)	
Lower explosion limit : Typical 1 %(V)	
Flammability (solid, gas) : Data not available	
Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable extinguishing : Do not use water in a jet. media	
<ul> <li>Specific hazards during firefighting</li> <li>Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulate gases (smoke). Carbon monoxide may be evolved if incomplete combus occurs. Unidentified organic and inorganic compounds.</li> </ul>	
Specific extinguishing : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	I

\_

Version 1.3		Revision Date 23.08.2016	Print Date 25.08.2016
Further information	:	Flammable liquid.	
Special protective equipment for firefighters	:	Proper protective equipment includ gloves are to be worn; chemical re- large contact with spilled product is Breathing Apparatus must be worn a confined space. Select fire fighte relevant Standards (e.g. Europe: E	sistant suit is indicated if expected. Self-Contained when approaching a fire in r's clothing approved to

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and	:	Avoid contact with skin and eyes.
emergency procedures Environmental precautions	:	Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Chapter 13 of this Safety Data Sheet.

### 7. HANDLING AND STORAGE

Advice on safe handling: Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.Avoidance of contact: Strong oxidising agents.	General Precautions	Use local exhaust ventilation if there is risk of inhalation vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disp this material.	
Avoidance of contact : Strong oxidising agents.	Advice on safe handling	Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear shou worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning	
	Avoidance of contact	Strong oxidising agents.	

Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016
Product Transfer	<ul> <li>This material has the potential to be a Proper grounding and bonding proced during all bulk transfer operations.</li> </ul>	
Storage		
Other data	<ul> <li>Keep container tightly closed and in a cool, well-ventilated place.</li> <li>Use properly labeled and closable containers.</li> </ul>	
	Store at ambient temperature.	
Packaging material	<ul> <li>Suitable material: For containers or constant</li> <li>steel or high density polyethylene.</li> <li>Unsuitable material: PVC.</li> </ul>	ontainer linings, use mild
Container Advice	Polyethylene containers should not be temperatures because of possible risk	

## 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source
Oil mist, mineral	Not Assigned	TWA ((inhalable fraction))	5 mg/m3	US. ACGIH Threshold Limit Values

### Components with workplace control parameters

### **Biological occupational exposure limits**

No biological limit allocated.

### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany

Ondina X 420		
Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016
http://www.dguv.de/inhalt/in	dex.jsp	
L'Institut National de Reche	rche et de Securité, (INRS), France http:/	//www.inrs.fr/accueil
<section-header></section-header>	<ul> <li>The level of protection and types vary depending upon potential exp controls based on a risk assessme Appropriate measures include: Adequate ventilation to control airl Where material is heated, sprayed greater potential for airborne conc</li> <li>General Information: Define procedures for safe handlir controls.</li> <li>Educate and train workers in the h measures relevant to normal activ product.</li> <li>Ensure appropriate selection, testi equipment used to control exposu equipment, local exhaust ventilation Drain down system prior to equipm maintenance.</li> <li>Retain drain downs in sealed stora subsequent recycle.</li> <li>Always observe good personal hy washing hands after handling the drinking, and/or smoking. Routine protective equipment to remove co contaminated clothing and footwea Practice good housekeeping.</li> </ul>	bosure conditions. Select ent of local circumstances. borne concentrations. d or mist formed, there is centrations to be generated. Ing and maintenance of mazards and control rities associated with this ing and maintenance of ire, e.g. personal protective on. ment break-in or age pending disposal or giene measures, such as material and before eating, ely wash work clothing and ontaminants. Discard

## Personal protective equipment

## Protective measures

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker	precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an
---	---

Hand protection

rsion 1.3	Revision Date 23.08.2016	Print Date 25.08.2016	
Remarks	gloves approved to relevant stand US: F739) made from the followin suitable chemical protection. PVC gloves Suitability and durability of usage, e.g. frequency and duratic resistance of glove material, dexte from glove suppliers. Contaminate replaced. Personal hygiene is a k care. Gloves must only be worn o gloves, hands should be washed	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.	
	For continuous contact we recom breakthrough time of more than 2 for > 480 minutes where suitable short-term/splash protection we re recognize that suitable gloves offer may not be available and in this of time maybe acceptable so long as and replacement regimes are follor a good predictor of glove resistan dependent on the exact composit Glove thickness should be typical depending on the glove make and	40 minutes with preference gloves can be identified. For ecommend the same, but ering this level of protection ase a lower breakthrough s appropriate maintenance owed. Glove thickness is not ce to a chemical as it is ion of the glove material. ly greater than 0.35 mm	
Eye protection	: If material is handled such that it of protective eyewear is recommend		
Skin and body protection	: Skin protection is not ordinarily re work clothes. It is good practice to wear chemic		
Thermal hazards	: Not applicable		
Environmental exposure c	ontrols		
General advice	: Take appropriate measures to full relevant environmental protection contamination of the environment Chapter 6. If necessary, prevent being discharged to waste water. treated in a municipal or industria before discharge to surface water	legislation. Avoid by following advice given in undissolved material from Waste water should be I waste water treatment plant	

before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Liquid at room temperature.
Colour	: clear
Odour	: Slight hydrocarbon

# Safety Data Sheet

# Ondina X 420

rsion 1.3	Revision Date 23.08.2016	Print Date 25.08.2016
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: -36 °C / -33 °FMethod: ISO 3016	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)	
Flash point	: 225 °C / 437 °F Method: ISO 2592	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Data not available	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0,5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Relative density	: 0,816 (15 °C / 59 °F)	
Density	: 816 kg/m3 (15,0 °C / 59,0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: Pow: > 6,5	
Auto-ignition temperature	: > 320 °C / 608 °F	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 40 mm2/s (20 °C / 68 °F) Method: ISO 3104	
	4,1 mm2/s (100 °C / 212 °F) Method: ISO 3104	
	18 mm2/s (40,0 °C / 104,0 °F) Method: ISO 3104	
Explosive properties	: Not classified	

# Safety Data Sheet

## Ondina X 420

Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016
Oxidizing properties	: Data not available	
Conductivity Decomposition temperature	<ul><li>This material is not expected to be</li><li>Data not available</li></ul>	e a static accumulator.

### **10. STABILITY AND REACTIVITY**

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	Hazardous decomposition products are not expected to form during normal storage.

## **11. TOXICOLOGICAL INFORMATION**

Basis for assessmen	t :	Information given is based on product testing, and/or similar products, and/or components.
Information on likely exposure	routes of :	Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity		
Product:		
Acute oral toxicity	:	LD50 rat: > 5.000 mg/kg Remarks: Low toxicity:
Acute inhalation toxic	city :	LC 50 Rat: > 5 mg/l Exposure time: 4 h Remarks: Low toxicity by inhalation.
Acute dermal toxicity	:	Rat: Remarks: Low toxicity: LD50 >2000 mg/kg

### Skin corrosion/irritation

Product:

Version 1.3

Revision Date 23.08.2016

Print Date 25.08.2016

Remarks: Not irritating to skin.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Not irritating to eye.

### Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser.

#### Germ cell mutagenicity

#### Product:

Remarks: Not expected to be mutagenic.

#### Carcinogenicity

### Product:

Remarks: Not expected to be carcinogenic.

Material	GHS/CLP Carcinogenicity Classification
Distillates (Fischer-Tropsch), heavy, C18-50- branched and linear	No carcinogenicity classification.

### **Reproductive toxicity**

### Product:

Remarks: Does not impair fertility., Not a developmental toxicant.

#### STOT - single exposure

### Product:

Remarks: Not expected to be a hazard.

### STOT - repeated exposure

### Product:

Remarks: Not expected to be a hazard.

#### Aspiration toxicity

Version 1.3

Revision Date 23.08.2016

Print Date 25.08.2016

### Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Further information**

### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION	
Basis for assessment	: Information given is based on product testing.
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to crustacean (Acute toxicity)	: Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic toxicity)	: Remarks: NOEC/NOEL > 100 mg/l
Toxicity to crustacean (Chronic toxicity)	: Remarks: NOEC/NOEL > 100 mg/l
(Acute toxicity) (Acute toxicity)	: Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Persistence and degradability	
Product:	
Biodegradability	: Remarks: Expected to be inherently biodegradable.
Bioaccumulative potential	
Product:	
Bioaccumulation	: Remarks: Does not bioaccumulate significantly.
Partition coefficient: n- octanol/water	: Pow: > 6,5

••••••••		
Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016
Mobility in soil		
Product:		
Mobility	<ul> <li>Remarks: Liquid under most environ enters soil, it will adsorb to soil parti mobile.</li> <li>Remarks: Floats on water.</li> </ul>	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	<ul> <li>Product is a mixture of non-volatile expected to be released to air in an Not expected to have ozone depleti photochemical ozone creation poten potential.</li> <li>Films formed on water may affect o damage organisms., May cause phy organisms.</li> </ul>	y significant quantities., ion potential, ntial or global warming xygen transfer and

### **13. DISPOSAL CONSIDERATIONS**

Disposal methods	
Waste from residues	: Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

### **14. TRANSPORT INFORMATION**

### International Regulations

ADR Not regulated as a dangerous good ADN Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

Version 1.3

Revision Date 23.08.2016 Print Date

Print Date 25.08.2016

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Pollution category Ship type Product name Special precautions	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>
Special precautions for user	
Remarks	: Special Precautions: Refer to Chapter 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: MARPOL Annex 1 rules apply for bulk shipments by sea.

#### **15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Other international regulations

he components of this product are reported in the following inventories:
--

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.

#### **16. OTHER INFORMATION**

Full text of H-Statements					
H304 Ma	y be fatal if swallowed and enters airways.				
Full text of other abbrevia	tions				
Asp. Tox. As	spiration hazard				
Abbreviations and Acronym	s : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.				
SDS Regulation	<ul> <li>Regulation 1907/2006/EC</li> <li>1. GN 2.2.5.1313-03 "Maximum permissible concentration of harmful substance in the working zone area".</li> <li>2. GOST 12.1.007-76 "Harmful agents.Classification and safety requirements."</li> <li>3. GOST 12.1.005-88 "General hygiene requirements to the working zone area".</li> <li>4. GN 2.1.5.1315-03 "Reservoir water maximum permissible concentration".</li> <li>5. GOST 19433-88 "Dangerous goods. Classification and</li> </ul>				

Version 1.3	Revision Date 23.08.2016	Print Date 25.08.2016			
	accidents liquidation procedur	<ol> <li>Rail transportation safety rules and dangerous goods accidents liquidation procedure.</li> <li>GOST 30333-2007 Chemical product safety data</li> </ol>			
Further information					
Other information	: A vertical bar ( ) in the left margin in from the previous version.	ndicates an amendment			

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.